

## POLYURETHANE CHAIR WITH MEDIUM BACK – HIGH BENCH HEIGHT SPECIFICATIONS



PHBCH-MB-RG

<b>Pneumatic Adjustment</b>	24½-33½" (62.23-85.09 cm) Adjustable height measured from the top of the seat to the floor
<b>Seat Width</b>	16" (40.64 cm)
<b>Seat Depth</b>	17" (43.18 cm)
<b>Seat Thickness</b>	1½" (3.81 cm)
<b>Back Width</b>	15 ½" (39.37 cm)
<b>Back Height</b>	14 ½" (36.83 cm)
<b>Back Thickness</b>	1" (2.54 cm)
<b>Arm Rests (optional)</b>	6-way adjustable arm rests support a variety of arm placements for proper ergonomics. Adjustable arm rests move up and down, in and out, and twist toward or away from the user.
<b>Inside Width Between Arms</b>	17-19 ½" (43.18-49.53 cm)
<b>Upward Arm Adjustment</b>	3 ½" (8.89 cm)
<b>Arm Pad Length</b>	9" (22.86 cm)
<b>Arm Pad Width</b>	3 ½" (8.89 cm)

<b>Arm Pad Thickness</b>	1 3/4" (4.45 cm)
<b>Seat Material</b>	Rugged polyurethane that is self-skinning, chemical- and puncture-resistant, easily cleaned, and soil resistant
<b>Seat Tilt (optional)</b>	Ergonomic 8° forward and 3° backward seat tilt locks in place
<b>Foot ring</b>	18 1/4" (46.36 cm) diameter black, durable nylon reinforced fiberglass or 20" diameter chrome
<b>Casters/Glides</b>	Available in black rolling, non-marring casters (suitable for both hard and carpeted floors) or black, non-marring bell glides (suitable for both hard and carpeted floors)
<b>Base</b>	25" (63.5 cm) 5-leg nylon reinforced fiberglass
<b>Weight Capacity</b>	300 lbs (136.08 kg)
<b>Warranty</b>	15 year parts, lifetime on pneumatic lift